

ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):				GIO	IA 470	AZ					
Indirect heating functionality:					no						
Direct heat output:					5,6						
Indirect heat output:					-						
Fuel	Preferred fuel (only	Other suitable	η _s [%]:	emi	Space ssions neat ou	at non	ninal	emis	Space ssions at outp	at mini	mum
	one):	fuel(s):	·15 [/ •].	PM	OGC		$NO_{\rm x}$	PM	OGC	со	NO _x
				m	g/Nm ³	(13%0	D ₂)	mg	g/Nm3	(13%O2)	
Wood logs with moisture content ≤ 25 %	yes	no	76	10	32	609	103	n.p.	n.p.	n.p.	n.p.
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO) Tel. +39.051.459.3.111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it Pl. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.



Item	Symbol	Value	Unit	Item	Symbol	Value	
eat output				Useful efficiency (NCV a	as receive	d)	
lominal heat output	P _{nom}	5,6	kW	Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	85,6	
/linimum heat output indicative)	P _{min}	N.A.	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{\text{th,min}}$	N.A.	
Auxiliary elettricity consum	nption			Type of heat output/roo one)	m tempera	ature cont	
At nominal heat output	el _{max}	n.p.	kW	/	single stage heat output, no room		
At minimum heat output	el _{min}	n.p.	kW		two or more manual stages, no room temperature control		
n standby mode	el _{SB}	n.p.	kW	with mechanic thermos temperature control	with mechanic thermostat room temperature control		
Permanent pilot flame pow	er require	ement		with eletronic room ten control	npearture	no	
Pilot flame power equirement (if applicable) P _{pilot} n.p. kW with eletronic room tempea control plus day timer			no				
				with eletronic room ten control plus week timer	npearture	no	
				Other control options (n	nultiple se	elections p	
				room temperature cont presence detector	trol, with	no	
				room temperature cont open window detection	trol, with	no	
				with distance control optic	on	no	
Contact details	Na	me and a	address o	f the manufacturer or its auth	norised re	epresenta	
+39 0522 972260				CORISIT SRL			
- info@corisit.com				Via Enrico Fermi, 5 (Z.I. Rame 42046 Reggiolo (RE) - Italy	e)		
www.corisit.com				Italy	•.		

Characteristics when operating with the preferred fuel only:

(*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO_x = nitrogen oxides

(**) Only required if correction factors F(2) or F(3) are applied

Approved by Maurizio Lorenzon Lab manager

porenton plaunte



Kiwa Cermet Italia S.p.A. Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl Sede legale: Via Cadriano 23, 40057 Granarolo dell'Emilia (BO) Tel. +39.051.459.3.111 - Fax +39.051.763.382 - info@kiwacermet.it - www.kiwacermet.it Pl. 00627711203 - C.F. 03502820370 - Capitale Sociale: € 1.000.000,00 i.v.